



## IDU-BS-G(60W)

**IDU-BS-G(60W)** is an indoor AC/DC PoE injector with built-in lightning protection compatible with all InfiNet Wireless units. PoE injector is powered by an AC supply in the 100-240 V range. Built-in lightning protection protects units connected to **IDU-BS-G(60W)**.

### Key Features

- ▶ Supplied by default with InfiLINK XG, InfiLINK XG 1000 families and R5000-Qmxb model of the InfiMAN 2x2 family
- ▶ Compatible with all InfiNet Wireless units
- ▶ Indoors installations only
- ▶ Built-in lightning protection

# IDU-BS-G(60W)

## Technical Specification



Parameter	Description
Compatible models	All InfiNet Wireless units
Input Voltage (AC)	100 ... 240 V
Output Voltage	+55 V
Power Consumption	60 W
Pin Assignment and Polarity	<ul style="list-style-type: none"><li>Data Pairs 1/2 (-) and 3/6 (+)</li><li>Spare Pairs 7/8 (-) and 4/5 (+)</li></ul>
Supported Ethernet Modes	10/100/1000 Mbps (Gigabit Ethernet)
Operating temperature range	-10...+40 °C
Size and Weight	151x62x38 mm, 0.32 kg
Electromagnetic compatibility	Conforms to: <ul style="list-style-type: none"><li>FCC Class B</li><li>EN55022 Class B</li></ul>
Lightning protection	In compliance with: <ul style="list-style-type: none"><li>IEC 61000-4-2 (ESD) 15kB (air), 8kB (contact)</li><li>IEC 61000-4-4 (EFT) 40A (tp = 5/50ns)</li><li>IEC 61000-4-5 (Lightning) L5, 95A (tp = 8/20us)</li></ul>

## Connection Scheme

