


InfiLINK Evolution E5-ST25

Description	InfiLINK Evolution E5-ST25, 5 GHz point-to-point unit, net throughput up to 670 Mbps, integrated dual-pol antenna, 25 dBi, 8x8 deg
Net throughput	up to 670 Mbps
Recommended distances	up to 25 km
Radio technology	MIMO 2x2 (OFDM 64/128)
Modulation coding schemes	from BPSK 1/2 to QAM256 5/6
Transmit power	up to 25 dBm
Receiver sensitivity	down to -90 dBm
Frequency range	4900-6050 MHz
Channel width	20, 40, 80 MHz
Center frequency adjustment step	125 kHz
Duplex scheme	TDD
Antenna	25 dBi
Wired Interfaces	1x GigabitEthernet (RJ45)



InfiLINK Evolution E5-ST25

Consumption	up to 15 W			
Power options	90-240 VAC ~ @ 50/60 Hz, ±43..56 VDC			
Outdoor Unit (ODU)	350x350x71,5 mm, 2.3 kg			
				
Part Number Options	Prefix	Freq. Band	Ant.	Capacity
				20
	<i>E</i>	<i>5</i>	<i>25</i>	50 670
Part Number Example	E5-ST25/06500 50			
Packing List	<ul style="list-style-type: none"> - Outdoor unit E5-ST25 - 1 pcs. - Power Supply IDU-CPE-G(24W) - 1 pcs. - Power Cord - 1 pcs. - Cable Gland - 1 pcs. - Standard RJ-45 connector - 1 pcs. - Shielded RJ-45 connector - 1 pcs. - RJ-45 Plug Cap - 1 pcs. - MONT-KIT-85 Mounting kit - 1 pcs. - Quick Start Guide - 1 pcs. 			



InfiLINK Evolution E5-ST25

Features

RADIO

- ▶ Voice/RTP Aware Superpacketing
- ▶ DFS
- ▶ Automatic Bitrate Control
- ▶ Automatic Transmit Power Control
- ▶ Spectrum Analyzer mode
- ▶ Channel testing tools

NETWORKING

- ▶ Ethernet-over-IP and IP-over-IP tunneling
- ▶ ARP protocol support
- ▶ MAC/IP filtering
- ▶ Full-fledged 2nd layer switch
- ▶ RIPv2 / OSPFv2 /static routing
- ▶ L2/L3 Firewall
- ▶ NAT (multipool, H.323-aware)
- ▶ DHCP client/server/relay

MANAGEMENT FEATURES

- ▶ Various Management Protocols: HTTP, HTTPS, SSH, Telnet, SNMP v1/2c/3 (MIB-II and proprietary MIBs)
- ▶ Graphical User Interface
- ▶ LED Indication: power status, wireless and wired link status, signal level
- ▶ Antenna alignment tool
- ▶ Automatic software update
- ▶ Online monitoring with proprietary EMS InfiMONITOR.

QUALITY-OF-SERVICE

- ▶ 17 priority queues
- ▶ IEEE 802.1p support
- ▶ IP TOS / DiffServ support
- ▶ Full voice support
- ▶ Traffic limiting (absolute, relative, mixed)
- ▶ Traffic redirection



InfiLINK Evolution E5-ST25

Features

ENVIRONMENTAL

- ▶ **Outdoor Units:**
 - operating temperature range -40..+60 °C, (can be extended to -55..+60 °C, models with "t" index in PN), 100% humidity, condensing
 - IP66/IP67 compliant water and dust protection
 - wind load: 200 kph, survival
- ▶ **Indoor Unit:**
 - 0..+40 °C, 95% humidity, non-condensing

SECURITY FEATURES

- ▶ **Storm/flood protection**
- ▶ **Password protection**
- ▶ **Secure command-line access via SSH protocol**

MAC

- ▶ **ARP support**
- ▶ **Proactive channel testing**
- ▶ **Pseudo-radio interface:**
 - unique Infinet Wireless feature to join Infinet networks via 3rd party equipment
- ▶ **Automatic over-the-air firmware upgrade**

STANDARD COMPLIANCE

- ▶ **Radio**
 - ETSI EN 301 893 v.2.1.1
 - ETSI EN 302 502 v.2.1.3
 - FCC Part 15.407
- ▶ **EMC**
 - ETSI EN 301 489-1 v.2.2.3
 - ETSI EN 301 489-17 v.3.2.4
 - FCC Part 15 Class B
- ▶ **Safety**
 - EN 62368-1:2014+A11:2017
 - EN60950-22:2017
 - EN62311:2008
- ▶ **RoHS (pending)**
 - EN IEC 63000:2018



InfiLINK Evolution E5-ST25

Radiation diagram

