


Xm/5X.1000.4x300.2x26

| | |
|---|---|
| Description | InfiLINK XG 1000 Xm/5X.1000.4x300.2x26, 5 GHz point-to-point unit, net throughput up to 1000 Mbps, integrated dual-pol antenna, 26 dBi, 8x8 deg |
| Net throughput | up to 1000 Mbps |
| Recommended distances | up to 40 km |
| Radio technology | MIMO 2x2, Cyclic single carrier |
| Modulation coding schemes | from QPSK 1/4 to QAM1024 8/10 |
| Transmit power | up to 25 dBm |
| Receiver sensitivity | down to -92 dBm |
| Frequency range | 4900-6000 MHz |
| Channel width | 2x10, 2x20, 2x40 MHz |
| Center frequency adjustment step | 1 MHz |
| Duplex scheme | TDD |
| Antenna | 26 dBi |
| Wired Interfaces | 2x GigabitEthernet, SFP |



Xm/5X.1000.4x300.2x26

| | |
|--------------------|---|
| Consumption | up to 55 W |
| Power options | 90-240 VAC @ 50/60 Hz, 43..56 VDC |
| Outdoor Unit (ODU) | 371 x 371 x 89 mm, 3.3 kg |
| |  |
| Packing List | <ul style="list-style-type: none"> - Outdoor unit Xm/5X.1000.4x300.2x26 - 1 pcs. - Power Supply IDU-CPE-G(56W) - 1 pcs. - Power Cord - 1 pcs. - Cable Gland for RJ-45 - 2 pcs. - Cable Gland for optical cable - 1 pcs. - Standard RJ-45 connector - 2 pcs. - Shielded RJ-45 connector - 1 pcs. - RJ-45 P |



Xm/5X.1000.4x300.2x26

Features

RADIO

- ▶ **Best-in-breed spectral efficiency**
 - up to 12,5 bps/Hz
- ▶ **Flexible frequency planning**
 - utilizing two non-adjacent frequency channels
 - support of TDD and Hybrid-FDD
- ▶ **Reliable signal receiving in both LOS and NLOS conditions**
- ▶ **TDD synchronization using a built-in GNSS receiver**

NETWORKING

- ▶ **Built-in full-fledged L2 switch supporting VLAN and STP**
- ▶ **Transparent L2 transport for Ethernet traffic of any type**

MANAGEMENT FEATURES

- ▶ **Web-based graphical user interface**
- ▶ **Command line interface**
- ▶ **SNMP v1/2c/3 support (MIB-II and proprietary MIBs)**
- ▶ **Centralized monitoring using EMS InfiMONITOR.**

QUALITY-OF-SERVICE

- ▶ **QoS support:**
 - 4 priority queues: strict and weighted prioritisation
 - Classification based on IEEE 802.1p
 - Egress rate limiting on each network port

INSTALLATION AND DIAGNOSTIC TOOLS

- ▶ **LED indication**
 - power status
 - wired and wireless link status
 - received signal strength indication
 - TDD sync status
- ▶ **Web GUI tools**
 - antenna alignment tool
 - spectrum analyzer



Xm/5X.1000.4x300.2x26

Features

ENVIRONMENTAL

- ▶ **Outdoor unit:**
 - operating temperature range -40..+60 °C, (can be extended to -55..+60 °C, models with "t" index in PN)
 - IP66/IP67 compliant water and dust protection
 - wind load: 200 kph, survival
- ▶ **Indoor unit**
 - 0..+40 °C
 - 90-240 VAC ~ @ 50/60 Hz or ±43..±56 VDC
 - power consumption up to 60 W

STANDARD COMPLIANCE

- ▶ **Safety:**
 - EN 60950-1:2006, UL 60950-1 2nd ed.
- ▶ **Radio (pending):**
 - EN 301 893 v.2.1.1, EN 302 502, v.2.1.1, FCC part 15.247
- ▶ **EMC:**
 - ETSI EN 301 489-1, ETSI EN 301 489-17, FCC Part 15 Class B
- ▶ **RoHS:**
 - Directive 2011/65/EU

